

Technical drawing of a double-row roller bearing assembly. The drawing shows a cross-section of the bearing with dimensions in millimeters (mm) and inches (in).

Dimensions (mm / in):

- 30
- 6 10
- 5 9
- 113
- DW=900 (810)
- 8
- 30
- 19
- 19
- 30
- DW=900 (810)

Overall dimensions (mm / in):

- 有効開口寸法 = 864 (774)
- 30
- 5
- 枠内 = 1,764 (1,584)
- 枠外 = 1,824 (1,644)
- 5
- ROW = 1,834 (1,654)

Technical drawing of a double-door window frame. The drawing shows a cross-section of the frame with two doors. Dimensions are given in millimeters (mm). The overall height is 165 mm. The frame has a width of 9 mm. The door height is 110 mm. The door width is 30 mm. The door thickness is 8 mm. The door is divided into three sections: 19 mm, 19 mm, and 19 mm. The door is labeled with 4.5, 4.5, and 4.5. The door is labeled with 18. The door is labeled with 6. The door is labeled with 13.5. The door is labeled with 30. The door is labeled with 8.5. The door is labeled with DH=2,348. The door is labeled with 枠内=2,370. The door is labeled with 枠外=2,400. The door is labeled with 12.

[illegible]

平面図

18 18

3 15 15 3

30

振れ止め金具 (床用)

縦枠芯

2.5 2.5

5